

# AZENIS FK510

- Falken's latest generation most high performance summer tire, the AZENIS FK510 is designed for drivers of premium vehicles looking for excellent grip and outstanding performance.
- 4D Nano Design enables Falken engineers to optimize new high-performance compounds at the molecular level, enhancing both wear and wet weather traction.
- Featuring hybrid undertread materials, the FK510 delivers handling and stability.



**AZENIS FK510**

Rim (inch)	Aspect ratio (%)	Tire Size	Load Index	Speed Symbol	XL or RF	TL or TT	E-No.	Overall Diam. (mm)	Section Width (mm)	Rim Width (code)		Tread Depth (mm)
										Measuring	Approved	
22	25	295 /25 ZR 22	97	Y	○	TL		707	306	10.50	10.00 - 11.00	7.3
	21	255 /30 ZR 21	(93)	(Y)	○	TL	○	687	263	9.00	8.50 - 9.50	7.7
21	30	295 /30 ZR 21	(102)	(Y)	○	TL	○	713	306	10.50	10.00 - 11.00	7.3
		225 /35 ZR 21	(90)	(Y)	○	TL	○	666	232	8.00	7.50 - 9.00	7.8
	35	235 /35 ZR 21	(92)	(Y)	○	TL	○	672	244	8.50	8.00 - 9.50	7.8
		245 /35 ZR 21	(96)	(Y)	○	TL	○	705	251	8.50	8.00 - 9.50	7.8
		265 /35 ZR 21	(101)	(Y)	○	TL	○	721	275	9.50	9.00 - 10.50	7.6
		285 /25 ZR 20	93	Y	○	TL	○	650	300	10.50	10.50 - 10.50	7.3
20	25	295 /25 ZR 20	(95)	(Y)	○	TL	○	656	306	10.50	10.00 - 11.00	7.3
		235 /30 ZR 20	(88)	(Y)	○	TL	○	650	244	8.50	8.50 - 8.50	7.7
	30	245 /30 ZR 20	(90)	(Y)	○	TL	○	656	251	8.50	8.00 - 9.00	7.8
		255 /30 ZR 20	(92)	(Y)	○	TL	○	662	263	9.00	8.50 - 9.50	7.7
		265 /30 ZR 20	(94)	(Y)	○	TL	○	668	275	9.50	9.00 - 10.00	7.5
		275 /30 ZR 20	(97)	(Y)	○	TL	○	674	282	9.50	9.00 - 10.00	7.5
		285 /30 ZR 20	(99)	(Y)	○	TL	○	680	295	10.00	9.50 - 10.50	7.3
		295 /30 ZR 20	(101)	(Y)	○	TL	○	688	306	10.50	10.00 - 11.00	7.3
	35	225 /35 ZR 20	(90)	(Y)	○	TL	○	666	232	8.00	7.50 - 9.00	7.8
		235 /35 ZR 20	(92)	(Y)	○	TL	○	672	244	8.50	8.00 - 9.50	7.8
		245 /35 ZR 20	(95)	(Y)	○	TL	○	680	251	8.50	8.00 - 9.50	7.8
		255 /35 ZR 20	(97)	(Y)	○	TL	○	688	263	9.00	8.50 - 10.00	7.8
265 /35 ZR 20		(99)	(Y)	○	TL	○	696	275	9.50	9.00 - 10.50	7.7	
275 /35 ZR 20		(102)	(Y)	○	TL	○	702	282	9.50	9.00 - 11.00	7.6	
40	285 /35 ZR 20	(104)	(Y)	○	TL	○	710	295	10.00	9.50 - 11.00	7.4	
	315 /35 ZR 20	110	Y	○	TL	○	730	326	11.00	10.50 - 12.50	7.2	
	245 /40 ZR 20	(99)	(Y)	○	TL	○	706	251	8.50	8.00 - 9.50	7.9	
	255 /40 ZR 20	(101)	(Y)	○	TL	○	714	263	9.00	8.50 - 10.00	7.9	
	265 /40 ZR 20	104	Y	○	TL	○	722	275	9.50	9.00 - 10.50	7.7	
	275 /40 ZR 20	(106)	(Y)	○	TL	○	730	282	9.50	9.00 - 11.00	7.7	
45	245 /45 ZR 20	103	Y	○	TL	○	730	246	8.00	7.50 - 9.00	7.9	
	255 /45 ZR 20	105	Y	○	TL	○	742	258	8.50	8.00 - 9.50	7.9	
50	255 /50 ZR 20	109	Y	○	TL	○	768	269	8.00	7.00 - 9.00	7.9	
	245 /30 ZR 19	(89)	(Y)	○	TL	○	631	251	8.50	8.00 - 9.00	7.7	
19	30	255 /30 ZR 19	(91)	(Y)	○	TL	○	637	263	9.00	8.50 - 9.50	7.7
		265 /30 ZR 19	(93)	(Y)	○	TL	○	643	275	9.50	9.00 - 10.00	7.5
	35	275 /30 ZR 19	(96)	(Y)	○	TL	○	649	282	9.50	9.00 - 10.00	7.5
		285 /30 ZR 19	(98)	(Y)	○	TL	○	655	295	10.00	9.50 - 10.50	7.3
		295 /30 ZR 19	100	Y	○	TL	○	663	306	10.50	10.00 - 11.00	7.5
		215 /35 ZR 19	85	Y	○	TL	○	633	220	7.50	7.00 - 8.50	7.8
		225 /35 ZR 19	(88)	(Y)	○	TL	○	641	232	8.00	7.50 - 9.00	7.8
		235 /35 ZR 19	(91)	(Y)	○	TL	○	647	244	8.50	8.00 - 9.50	7.9
	40	245 /35 ZR 19	(93)	(Y)	○	TL	○	655	251	8.50	8.00 - 9.50	7.8
		255 /35 ZR 19	(96)	(Y)	○	TL	○	663	263	9.00	8.50 - 10.00	7.8
		265 /35 ZR 19	(98)	(Y)	○	TL	○	671	275	9.50	9.00 - 10.50	7.6
		275 /35 ZR 19	(100)	(Y)	○	TL	○	677	282	9.50	9.00 - 11.00	7.6
285 /35 ZR 19		(103)	(Y)	○	TL	○	685	295	10.00	9.50 - 11.00	7.4	
295 /35 ZR 19		(104)	(Y)	○	TL	○	691	306	10.50	10.00 - 11.50	7.4	
40	225 /40 ZR 19	(93)	(Y)	○	TL	○	665	232	8.00	7.50 - 9.00	7.9	
	235 /40 ZR 19	(96)	(Y)	○	TL	○	673	244	8.50	8.00 - 9.50	7.9	
	245 /40 ZR 19	(98)	(Y)	○	TL	○	681	251	8.50	8.00 - 9.50	7.9	
	255 /40 ZR 19	(100)	(Y)	○	TL	○	689	263	9.00	8.50 - 10.00	7.9	
	275 /40 ZR 19	(105)	(Y)	○	TL	○	705	282	9.50	9.00 - 11.00	7.7	

# AZENIS FK510

Rim (inch)	Aspect ratio (%)	Tire Size	Load Index	Speed Symbol	XL or RF	TL or TT	E-No.	Overall Diam. (mm)	Section Width (mm)	Rim Width (code)		Tread Depth (mm)
										Measuring	Approved	
19	45	225 /45 ZR 19	96	Y	○	TL	○	687	227	7.50	7.00 - 8.50	7.9
		235 /45 ZR 19	99	Y	○	TL	○	697	238	8.00	7.50 - 9.00	7.9
		245 /45 ZR 19	(102)	(Y)	○	TL	○	705	246	8.00	7.50 - 9.00	7.9
		255 /45 ZR 19	(104)	(Y)	○	TL	○	717	258	8.50	8.00 - 9.50	7.9
18	55	235 /55 ZR 19	105	Y	○	TL	○	745	248	7.50	6.50 - 8.50	7.9
		225 /35 ZR 18	(87)	(Y)	○	TL	○	615	232	8.00	7.50 - 9.00	7.9
	35	245 /35 ZR 18	92	Y	○	TL	○	629	251	8.50	8.00 - 9.50	7.8
		255 /35 ZR 18	(94)	(Y)	○	TL	○	637	263	9.00	8.50 - 10.00	7.8
		265 /35 ZR 18	(97)	(Y)	○	TL	○	645	275	9.50	9.00 - 10.50	7.6
		275 /35 ZR 18	(99)	(Y)	○	TL	○	651	282	9.50	9.00 - 11.00	7.6
		285 /35 ZR 18	(101)	(Y)	○	TL	○	659	295	10.00	9.50 - 11.00	7.4
		225 /40 ZR 18	(92)	(Y)	○	TL	○	639	232	8.00	7.50 - 9.00	8.0
	40	235 /40 ZR 18	(95)	(Y)	○	TL	○	647	244	8.50	8.00 - 9.50	8.0
		245 /40 ZR 18	(97)	(Y)	○	TL	○	655	251	8.50	8.00 - 9.50	8.0
		255 /40 ZR 18	(99)	(Y)	○	TL	○	663	263	9.00	8.50 - 10.00	7.9
		275 /40 ZR 18	99	Y	○	TL	○	679	282	9.50	9.00 - 11.00	7.7
45		225 /45 ZR 18	(95)	(Y)	○	TL	○	661	227	7.50	7.00 - 8.50	8.0
		235 /45 ZR 18	(98)	(Y)	○	TL	○	671	238	8.00	7.50 - 9.00	7.9
	245 /45 ZR 18	(100)	(Y)	○	TL	○	679	246	8.00	7.50 - 9.00	8.0	
	255 /45 ZR 18	103	Y	○	TL	○	691	258	8.50	8.00 - 9.50	7.9	
50	245 /50 ZR 18	(88)	(Y)	○	TL	○	707	256	7.50	7.00 - 8.50	7.9	
	40	245 /40 ZR 17	95	Y	○	TL	○	630	251	8.50	8.00 - 9.50	7.9
		255 /40 ZR 17	94	W	○	TL	○	638	263	9.00	8.50 - 10.00	7.9
45	275 /40 ZR 17	98	W	○	TL	○	654	282	9.50	9.00 - 11.00	7.7	
	215 /45 ZR 17	91	Y	○	TL	○	628	215	7.00	7.00 - 8.00	7.9	
	225 /45 ZR 17	94	Y	○	TL	○	636	227	7.50	7.00 - 8.50	8.0	
	235 /45 ZR 17	97	Y	○	TL	○	646	238	8.00	7.50 - 9.00	7.9	
	245 /45 ZR 17	99	Y	○	TL	○	654	246	8.00	7.50 - 9.00	7.9	
	205 /50 ZR 17	93	Y	○	TL	○	640	216	6.50	5.50 - 7.50	7.9	
50	225 /50 ZR 17	98	Y	○	TL	○	662	235	7.00	6.00 - 8.00	8.0	

# AZENIS FK510 RUNFLAT

Rim (inch)	Aspect ratio (%)	Tire Size	Load Index	Speed Symbol	XL or RF	TL or TT	E-No.	Overall Diam. (mm)	Section Width (mm)	Rim Width (code)		Tread Depth (mm)
										Measuring	Approved	
19	35	255 /35 RF 19	96	Y	○	TL	○	660	260	9.00	8.50 - 10.00	7.7
		275 /35 RF 19	100	Y	○	TL	○	674	278	9.50	9.00 - 11.00	7.7
40	225 /40 RF 19	93	Y	○	TL	○	662	230	8.00	7.50 - 9.00	7.7	
	245 /40 RF 19	98	Y	○	TL	○	678	248	8.50	8.00 - 9.50	7.7	
18	40	255 /40 RF 18	99	Y	○	TL	○	660	260	9.00	8.50 - 10.00	7.7
		275 /40 RF 18	103	Y	○	TL	○	676	278	9.50	9.00 - 11.00	7.7
45	225 /45 RF 18	95	Y	○	TL	○	658	225	7.50	7.00 - 8.50	7.7	
	245 /45 RF 18	100	Y	○	TL	○	676	243	8.00	7.50 - 9.00	7.7	
50	245 /50 RF 18	104	Y	○	TL	○	702	253	7.50	7.00 - 8.50	7.7	